



VX-350 SERIES

VHF/UHF Portable Radios



- 16 CHANNEL CAPACITY
- POWER OUTPUT : 5 W / 1 W (SELECTABLE)
- WIDE BAND COVERAGE
VHF 134-174 MHz
UHF 400-470 MHz / 450-520 MHz
- 8-CHARACTER ALPHANUMERIC DISPLAY (VX-354)
- 500 mW LOUD AUDIO WITH LARGE 36 mm SPEAKER
- LARGE CAPACITY 2000 mAh LI-ION BATTERY (FNB-V96LI)
- LONG BATTERY LIFE MORE THAN 15 HOURS* WITH RX/TX BATTERY SAVER CIRCUIT
- COMPACT AND RUGGED CONSTRUCTION
- WIDE/NARROW BANDWIDTH PER CHANNEL
- CTCSS / DCS ENCODE AND DECODE
- DTMF ANI
- 2-TONE ENCODE AND DECODE
- 5-TONE SIGNALING BUILT-IN
- EMERGENCY FEATURE
- VERSATILE SCAN (PRIORITY, DUAL WATCH, FOLLOW-ME AND TA SCAN)
- LONE WORKER FEATURE BUILT IN
 - STUN, KILL, REVIVE AND REMOTE LISTEN
 - ARTS™ (AUTO-RANGE TRANSPOND SYSTEM)
 - DTMF PAGING (OPTION)
 - ENCRYPTION (OPTION)
 - VOICE INVERSION
 - ROLLING CODE
 - MDC 1200® / GE-STAR® ANI (OPTION)
 - PC PROGRAMMING
 - RADIO-TO-RADIO CLONING

*FNB-V96LI/5-5-90 duty cycle w/saver

•Top



•Side

VX-354

Actual Size

VX-351



VX-350 SERIES VHF/UHF Portable Radio

LONG BATTERY LIFE MORE THAN 15 HOURS WITH 2000 mAh LI-ION BATTERY FNB-V96LI

The VX-350 Portables may be equipped with advanced FNB-V96LI Lithium-Ion Battery Packs with 2000 mAh of capacity, for operating times of more than 15 hours, even when using 5 Watts (5-5-90 duty cycle, w/saver).

Battery	Saver ON (RX:STBY 1:4)	Saver OFF
FNB-V96LI 2000 mAh	15.5 (15) hrs	13 (12.5) hrs
FNB-V95LI 1800 mAh	14 (13.5) hrs	11.7 (11.3) hrs

WIDE BANDWIDTH

For communicating with other agencies, companies, or even within your own communications system, the wide bandwidth of this radio will let you operate anywhere within the 40 MHz (VHF) or 70 MHz (UHF) band.

8-CHARACTER ALPHANUMERIC DISPLAY (VX-354)

Providing indication of either the channel number or an Alphanumeric Channel Label of up to 8 characters, the LCD display also provides convenient operation function icons to provide instant recognition of radio status. Including signal strength indicator and battery gauge.

500 mW LOUD AUDIO WITH LARGE 36 mm SPEAKER

Ideal for reception in noisy environments, the VX-350's high-powered audio is coupled to a large 36 mm internal speaker, assuring solid copy throughout difficult crowd control, fire, or sporting-event operations.

COMPACT AND RUGGED CONSTRUCTION

Weighing just 310 g and measuring just 58 x 105 x 33 mm (WHD) the VX-350 is ideal for business, industry, and public safety applications where light weight and compact size are important.

WIDE/NARROW BANDWIDTH PER CHANNEL

When programming radios for use in different jurisdictions, the VX-350 Series portables may be set up, channel by channel, for use in 12.5 kHz, 20 kHz, or 25 kHz channel spacing environments. Deviation and bandwidth are automatically set according to the configuration you choose.

BUILT-IN EMERGENCY FEATURE

With the built-in emergency feature, you are never alone. Any softkey can be programmed for Emergency operation. When activated, the radio will go to a designated channel, broadcast the unit ID and transmit live audio for pre-determined intervals.

2-TONE ENCODE AND DUAL 2-TONE DECODE

The VX-350 Series can transmit a 2-Tone paging call, and can receive 2-Tone calls using different tone combinations. For advanced network or fleet operations, a 5-Tone Encoder-Decoder circuit is included in the VX-350 Series.

DTMF ANI

A DTMF Automatic Number Identification string may be programmed into the VX-350, providing the dispatcher with a multiple-digit confirmation of the transmitting portable's identity.

DTMF PAGING (OPTION)

The optional FVP-25 board adds a DTMF paging decoder. With DTMF you can Stun, Kill and Alert.

ENCRYPTION (OPTION) VOICE INVERSION, ROLLING CODE

The FVP-35 and FVP-36 Encryption Units provide security for your important public safety and security communications. A DTMF Paging function is also included in the FVP-25 module, for selective calling.

MDC-1200® / GE-STAR® ANI ENCODE (OPTION)

Automatic Number Identification, triggered by the pressing of the PTT key, is available in the most popular industry-standard formats, via the optional VME-100.

OTHER FEATURES

- VERSATILE SCAN (PRIORITY, DUAL WATCH, FOLLOW-ME AND TA SCAN)
- CTCSS / DCS ENCODE AND DECODE
- ARTS™ (AUTO-RANGE TRANSPOND SYSTEM)
- PC PROGRAMMING
- RADIO-TO-RADIO CLONING

Applicable MIL-STD (Pending)

Standard	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures
Low Pressure	500.2/Procedure I, II	500.2/Procedure I, II	500.3/Procedure I, II
High Temperature	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II
Low Temperature	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II
Temperature Shock	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II
Rain	506.2/Procedure II	506.3/Procedure II	506.4/Procedure I, III
Humidity	507.2/Procedure II, III	507.3/Procedure II, III	507.4
Salt Fog	509.2	509.3	509.4
Dust	510.2/Procedure I	510.3/Procedure I	510.4/Procedure III
Vibration	514.3/Procedure Cat. 10	514.4/Procedure Cat. 10	514.5/Procedure Cat. 24
Shock	516.3/Procedure I	516.4/Procedure I	516.5/Procedure I

Specifications

	VHF	UHF
General Specification		
Frequency Range	134 -174 MHz	400 - 470 MHz 450 - 520 MHz
Number of Channels	16	
Power Supply Voltage	7.4 V DC ±20 %	
Channel Spacing	12.5/20/25 kHz	
Battery Life (5-5-90 duty) w/FNB-V96LI (2000mAh)	15.5 hrs (13 hrs w/o saver)	15 hrs (12.5 hrs w/o saver)
Operating Temperature Range	-30° C to +60° C	
Frequency Stability	±2.5 ppm	
RF Input-Output Impedance	50 Ohm	
Dimension (W x H x D)	58 x 105 x 33 mm	
Weight (Approx.)	310 g (w/FNB-V96LI, Antenna, Belt Clip)	

	VHF	UHF
Receiver Specification	measured by TIA/EIA-603	
Sensitivity (12dB SINAD)	0.25 µV	0.25 µV
Adjacent Channel Selectivity	65 / 60 dB (25 kHz/12.5 kHz)	
Intermodulation	65 / 60 dB (25 kHz/12.5 kHz)	
Spurious and Image Rejection	65 dB	
Audio Output	500mW @ 4 ohms 5% THD	
Transmitter Specification	measured by TIA/EIA-603	
Output Power	5 / 1 W	5 / 1 W
Modulation	16K0F3E, 11K0F3E	
Conducted Spurious Emission	65 dB below carrier	
FM Hum & Noise	45 / 40 dB (25 kHz/12.5 kHz)	
Audio Distortion	< 3 % @1kHz	

Specification may be changed without notification.

Accessories & Options

 MH-45B4B Noise Canceling Speaker Microphone	 MH-450S Speaker Microphone	 MH-360S Compact Speaker Microphone	 MH-37A4B Earpiece Microphone	 VC-25 VOX Headset	 FVP-25 Encryption / DTMF Paging Unit	 VME-100 MDC-1200®/GE-STAR® ANI Encode Unit	 FVP-36 Voice Inversion Encryption Unit	 FVP-35 Rolling Code Encryption Unit																																													
 FNB-V96LI 7.4 V 2000mAh Hi-Spec Li-Ion Battery Pack	 FNB-V95LI 7.4 V 1800mAh Standard Li-Ion Battery Pack	 VAC-300B/C/F* Desktop Rapid Charger (CD-34 + PA-42 B/C/F*)	 VAC-6300 6unit Multi Rapid Charger	 VCM-2 Vehicle Charger Mount Adaptor	 CT-27 Cloning Cable (Radio to Radio Cloning)	■ ANTENNA LIST																																															
LCC-350 Leather Case *B for 120 VAC, C for 230 VAC, F for 220-240 VAC Various accessories listed may not be available in some countries.						<table border="1"> <thead> <tr> <th>UHF</th> <th>ATU-6A</th> <th>400-430 MHz</th> <th>ATU-6DS</th> <th>450-485 MHz/3.5"</th> </tr> </thead> <tbody> <tr> <td></td> <td>ATU-6D</td> <td>450-490 MHz</td> <td>ATU-6F</td> <td>490-512 MHz</td> </tr> <tr> <th>VHF</th> <td>ATV-6A</td> <td>134-151 MHz/3.5"</td> <td></td> <td></td> </tr> <tr> <td></td> <td>ATV-6B</td> <td>150-163 MHz/3.5"</td> <td></td> <td></td> </tr> <tr> <td></td> <td>ATV-6C</td> <td>161-174 MHz/3.5"</td> <td></td> <td></td> </tr> <tr> <td></td> <td>ATV-6XL</td> <td>VHF UNTUNED</td> <td></td> <td></td> </tr> <tr> <td></td> <td>ATV-8A</td> <td>134-151 MHz</td> <td></td> <td></td> </tr> <tr> <td></td> <td>ATV-8B</td> <td>150-163 MHz</td> <td></td> <td></td> </tr> <tr> <td></td> <td>ATV-8C</td> <td>161-174 MHz</td> <td></td> <td></td> </tr> </tbody> </table>			UHF	ATU-6A	400-430 MHz	ATU-6DS	450-485 MHz/3.5"		ATU-6D	450-490 MHz	ATU-6F	490-512 MHz	VHF	ATV-6A	134-151 MHz/3.5"				ATV-6B	150-163 MHz/3.5"				ATV-6C	161-174 MHz/3.5"				ATV-6XL	VHF UNTUNED				ATV-8A	134-151 MHz				ATV-8B	150-163 MHz				ATV-8C	161-174 MHz		
UHF	ATU-6A	400-430 MHz	ATU-6DS	450-485 MHz/3.5"																																																	
	ATU-6D	450-490 MHz	ATU-6F	490-512 MHz																																																	
VHF	ATV-6A	134-151 MHz/3.5"																																																			
	ATV-6B	150-163 MHz/3.5"																																																			
	ATV-6C	161-174 MHz/3.5"																																																			
	ATV-6XL	VHF UNTUNED																																																			
	ATV-8A	134-151 MHz																																																			
	ATV-8B	150-163 MHz																																																			
	ATV-8C	161-174 MHz																																																			
Programming Cable	USB	FIF-10/A + CT-106	RS-232C	CT-29 + CT-28	Programming Software	CE86																																															



VERTEX STANDARD CO., LTD.

4-8-8 Nakameguro, Meguro-ku, Tokyo 153-8644, Japan

For our latest product news, visit us on the Internet:
<http://www.vxstd.com>

VERTEX STANDARD <http://www.vertexstandard.com>

US Headquarters

10900 Walker Street, Cypress, CA 90630, U.S.A.

YAESU EUROPE B.V.

P.O. Box 75525, 1118 ZN Schiphol, The Netherlands

YAESU UK LTD.

Unit 12, Sun Valley Business Park, Winnall Close

Winchester, Hampshire, SO23 0LB, U.K.

VERTEX STANDARD HK LTD.

Unit 5, 20/F., Seaview Centre, 139-141 Hoi Bun Road,

Kwun Tong, Kowloon, Hong Kong

VERTEX STANDARD AUSTRALIA PTY. LTD.

Normanby Business Park, Unit 14/45 Normanby Road

Notting Hill 3168, Victoria, Australia



2007.0405NA(EXP)

B9200566 Printed in Japan

www.radio-vertex.com.br